

校对清单

核对客户型号

比对基准参数

标注颜色/尺寸

材质

比对纸箱参数

A

B

C

D

E

F

G

H

SPECIFICATIONS
SPLIT AIR CONDITIONER

Qlima

Model outdoor		S 4626	
	Cooling	Heating	
Capacity *	kW	2.6	2.9
EE Class* / average season		A++	A+
SEER* / SCOP*		7.0	4.0
Air flow (nom.)	m³/h	1750	
Power supply	V / Hz	220-240~ / 50	
Refrigerant type / charge / GWP	kg	R32 / 0.550 / 675	
CO ₂ equivalent	tonnes	0.37	
Sound power level**	dB(A)	64	
Net weight	kg	23.2	
Maximum Allowable Pressure	MPa	4.4	
Excessive Operating Pressure suction / discharge	MPa	1.7/4.3	
RATED CURRENT	A	10	
RATED INPUT	W	2150	
Unit protection outdoor		IPX4	
Made in		PRC	
Serial number		AL01000001	

* EN 14511 / EN 14825 / ** EN 12102
Importer/Manufacturer:
PVG Holding B.V.,
Kanaalstraat 12 C,
5347 KM Oss, the Netherlands
P.O. Box 96, 5340 AB Oss,
the Netherlands | Qlima.com



Qlima S 4626
Contains fluorinated greenhouse gases covered by the Kyoto Protocol.
Hermetically sealed
Refrigerant: R32:0.550kg./675
Amount of refrigerant added by installation contractor: _____ kg.



Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere.



CAUTION

Qlima

1. Ensure to evacuate the air inside the indoor unit and pipes with a vacuum pump.
2. Make sure the additional amount of refrigerant to be charged is based on the pipe size and length. Please refer to the INSTALLATION MANUAL for details.
3. Incorrect installation will cause serious problems to the machine.

此流水号生产前
请联系制单提供

技术要求（版本号：E，2017-03）

1. 产品铭牌的外观质量、材料性能应符合QMK-J036.1006（QMZ-J53.008）《产品铭牌技术条件》的有关要求；
2. 字体、颜色要求应符合QMK-J016.2005《外销产品铭牌设计规范》（或QMK-J016.2004《内销产品铭牌设计规范》）的有关要求，或符合图纸标注要求；
3. 未注直线尺寸公差应符合GB/T1804-v；
4. 外协生产必须严格按电子文档进行输出；
5. 有RoHS指令要求的物料应符合美的企业标准QMK-J000.1002《产品中限制使用有害物质的技术标准》。
6. 有REACH要求的物料应符合QMK-J000.1008《REACH法规要求技术标准》。

Technical requirement(Ver.: E, 2017-03)

- 1.Appearance and material property of product nameplate shall comply with QMK-J036.1006（QMZ-J53.008） Technical Conditions for Product Nameplate;
- 2.Font and color shall comply with QMK-J016.2005 Design Code for Export Sales Product Nameplate (or QMK-J016.2004 Design Code for Domestic Sales Product Nameplate) or dimensioned requirement in drawing;
- 3.All undimensioned tolerances of linear dimensions shall comply with GB/T1804-v;
- 4.Out-sourced production shall be in strict accordance with electronic document;
- 5.Materials subject to RoHS shall comply with QMK-J000.1002 Technical Standard for Restricted Hazardous Substance in the Products of MIDEA.
- 6.Materials subject to REACH shall comply with QMK-J000.1008 Technical Standard for REACH of MIDEA.

16022000C59557

Qlima-KFR26W/BP3N8-X133(RD0)-GW-0406
(型号S 4626,带流水号,2021新商标)

铭牌

材料 艾利哑银PETt0.025+覆膜

标记 处数 更改文件号 签字 日期

绘图 赵春梅 审核 林灿荣

设计 赵春梅 标准化 林灿荣

校对 审定

会签 陈春泉 日期 2021.11.23

图样标记 重量 比例

共 1 页 第 1 页

广东美的制冷设备有限公司